

AMENDMENTS TO THE DRAWINGS:

The attached Replacement Sheet includes changes to Figure 2. This sheet replaces the original sheet containing Figures 1 and 2. No new matter has been added.

REMARKS

This Preliminary Amendment cancels, without prejudice, claims 1-7 in the underlying PCT Application No. PCT/EP2004/053554 and adds new claims 8-14. The new claims, inter alia, conform the claims to United States Patent and Trademark Office rules and do not add any new matter to the application.

In accordance with 37 C.F.R. § 1.125(b), the Substitute Specification (including the Abstract) contains no new matter. The amendments reflected in the Substitute Specification (including Abstract) are to conform the Specification and Abstract to United States Patent and Trademark Office rules or to correct informalities. As required by 37 C.F.R. §§ 1.121(b)(3)(ii) and 1.125(c), a Marked-Up Version of the Substitute Specification comparing the Specification of record and the Substitute Specification also accompanies this Preliminary Amendment. Approval and entry of the Substitute Specification (including Abstract) are respectfully requested.

The underlying PCT Application No. PCT/EP2004/053554 includes an International Search Report, dated May 3, 2005, a copy of which is included. The Search Report includes a list of documents that were considered by the Examiner in the underlying PCT application.

It is respectfully submitted that the subject matter of the present application is new, non-obvious, and useful. Prompt consideration and allowance of the application are respectfully requested.

Respectfully Submitted,

KENYON & KENYON LLP

By: *Gerard A. Messina* (a new 16091)
Michelle Carnicaro
Gerard A. Messina
Reg. No. 35,952

Dated: 22 Aug 2008

One Broadway
New York, NY 10004
(212) 425-7200
(212) 425-5288

CUSTOMER NO. 26646

1172176

DEVICE FOR IMPACT SENSING

~~Background of the Invention~~ FIELD OF THE INVENTION

The present invention is based on a device for impact sensing of the general type indicated in the independent patent claim.

5 BACKGROUND INFORMATION

~~From~~ German Patent Application No. DE 101 45 698 A1, 1 describes a sensor system for a vehicle ~~is known in which~~ acceleration sensors are situated on the bumper.

10 ~~Advantages of the Invention~~SUMMARY

~~In contrast, the~~ A device according to an example embodiment of the present invention for impact sensing having the features of the independent patent claim ~~has~~ may have the advantage that the acceleration sensor mechanism is situated between the crossmember of the bumper and the bumper fascia. A fixed connection of the acceleration sensor mechanism to the bumper fascia ~~is~~ may be particularly advantageous. Due to the installation location behind the bumper fascia, a reliable acquisition of acceleration signals is possible. The device according to the example embodiment of the present invention ~~is~~ may be particularly well-suited for recognizing pedestrians. The installation of the acceleration sensor mechanism in the bumper takes advantage of the fact that in the case of an accident involving a pedestrian the signal strength there increases significantly, because the acceleration sensor mechanism is situated closer to the point of impact, while on stretches of bad road the signal strength decreases due to a decoupling from the chassis. Accordingly, the installation location according to the present invention achieves a reliable and rapid recognition of a collision with a pedestrian.

~~Through the measures and developments stated in the dependent claims, advantageous improvements of the device for impact sensing indicated in the independent patent claim are possible.~~

- 5 It is particularly advantageous that the acceleration sensor mechanism has two acceleration sensors that are attached to the bumper fascia with an offset to the center of the vehicle. In this way, it is advantageously possible to reliably recognize a collision with a pedestrian that does not take place centrically.
- 10 In addition, the position of the impact can be determined. Furthermore, it is advantageous that at least one additional sensor mechanism is situated on the bumper. This can include for example a piezo cable having an integrated capacitive sensor, capable of recognizing not only a collision but also an approach to an obstacle
- 15 (i.e., an impending collision). Due to the combination of various sensor mechanisms, an even more reliable recognition of an impact with a pedestrian is possible. Distinguishing between a pedestrian and some other collision object is also made particularly simple.
- 20 ~~Normally, the~~The acceleration sensor mechanism for acquiring accelerations is typically configured in the longitudinal direction of the vehicle (x direction); however, it is possible to use a different sensing direction, for example the transverse direction of the vehicle (y direction) or the vertical direction
- 25 (z direction), or the x/y direction (angled), or an arbitrary combination of sensors in various directions.

- Finally, it ~~is~~may also be advantageous that the device is connected to a control apparatus for controlling equipment for protecting
- 30 persons, so that the control apparatus controls the protective equipment dependent on signals from the acceleration sensor mechanism and additional sensor mechanisms. In particular, besides the signal from the acceleration sensor mechanism, a signal representing the vehicle's inherent speed, or its speed relative
- 35 to the collision object, can also be used.

~~Drawing~~

BRIEF DESCRIPTION OF THE DRAWINGS

Exemplary embodiments of the present invention are shown in the ~~drawing figures~~, and are explained in ~~more~~further detail ~~in the following description below~~.

5 Figure 1 shows a top view of ~~the~~a device according to an example embodiment of the present invention, and.

Figure 2 shows a block diagram.

10
Description

DETAILED DESCRIPTION OF EXAMPLE EMBODIMENTS

Due to new legislation in the European Union, automobile
15 manufacturers are now required to reduce injuries to pedestrians in collisions with vehicles. This can be achieved on the one hand by constructing the front of the vehicle in such a way that the pedestrian is less seriously injured in such a collision. Thus, a passive solution is available. However, if the passive solution
20 is not sufficient, or is rejected as unsatisfactory, an active solution is pursued. Here, a sensor mechanism is used to recognize the impact with a pedestrian, and the protection of the pedestrian is then achieved by triggering suitable protective equipment, such as external airbags, or lifting the hood.

25 In this active solution, various sensor designs can be used. These include in particular the acceleration sensor. Acceleration sensors are already installed in the front of the vehicle in order to act as what are known as up-front sensors. These are installed
30 for example on the radiator supports. However, for protecting pedestrians this has the disadvantage that potholes, curb stones, and other uneven features of a road generate signals and amplitudes similar to those produced in a collision with a pedestrian. It is therefore fairly difficult to distinguish between an accident
35 involving a pedestrian and uneven features of the road.

According to an embodiment of the present invention, ~~it is~~
~~therefore proposed to situate~~ acceleration sensors are situated
between the bumper fascia and the crossmember of the bumper. In
5 this way, when there is a collision with a pedestrian the signal
is particularly high, and the decoupling from the chassis is such
that stretches of rough roadway and potholes generate only a low
signal.

10 With the aid of the example device according to the present
invention and a suitable evaluation of the signals produced by the
device, it is possible to distinguish between a collision with a
pedestrian and traveling over a section of bad road, as well as
other cases of false activation.

15 ~~In principle, the~~The device according to an example embodiment of
the present invention ~~operates~~may operate with one acceleration
sensor; however, it ~~is~~may be advantageous to use two acceleration
sensors having an offset to the right and to the left, for example
20 positioned 60cm from the center of the vehicle, in order to reliably
recognize pedestrian impacts that do not take place centrically
and to deliver positional data. Of course, it is possible to provide
still more acceleration sensors in order to achieve an even more
precise resolution.

25 In addition, it is possible to combine one or more acceleration
sensors behind the bumper fascia with other sensors, such as for
example a piezo cable or acceleration sensors at other installation
locations, such as a central sensor, or sensors fastened to
30 crossmembers or having other directions of measurement, for
example in the vertical direction of the vehicle. Likewise, the
knowledge of the vehicle's inherent speed, for example via the CAN
bus, or of its relative speed, for example via an environmental

sensor mechanism, can also be taken into account in the decision for the triggering of the protective equipment.

There are various possible ways of using the measured signals for up-front sensing. For example, information concerning the type of barrier (hard, soft, offset or complete coincidence), the relative speed between the automobile and the object, and the exact point in time of the impact can be used by the airbag algorithm.

10 Figure 1 shows a top view of the device according to the present invention. A bumper fascia 10 is situated in front of a foam 11 and crossmember 12. Acceleration sensors 14 are attached to bumper fascia 10, between bumper fascia 10, foam 11, and/or crossmember 12. In addition, here it is also possible to provide additional
15 acceleration sensors 13, as is done here for example on crossmember 12, one of the acceleration sensors also being capable of acquiring accelerations in the z direction. Acceleration sensors 14 acquire accelerations in the longitudinal direction of the vehicle.

20 Figure 2 visually represents the functioning of the device according to the present invention. The sensor signals of an acceleration sensor 20 that is situated at the left in the bumper, of a second acceleration sensor 21 situated at the right in the bumper, and of a central acceleration sensor 22 situated in the
25 airbag ECU, as well as an item of information relating to speed 23, are supplied to a control apparatus 24 having a data evaluation unit 25 and a function for distinguishing between pedestrians and stretches of bad roadway 26, in order to determine whether protective equipment such as an external airbag or an active engine
30 hood should be controlled. Besides the sensor inputs shown here, other sensor inputs are also possible. It is also possible to use fewer sensors than are indicated.

~~Abstract~~ABSTRACT

A device ~~is proposed~~ for impact sensing having an acceleration sensor mechanism on the bumper. The acceleration sensor mechanism
5 is situated between the bumper and a bumper fascia.
~~(Figure 2)~~